



MY 4



LY 1



LY 2

Main Technical Specifications

Specifications Model		MY4	LY1	LY2
Terminal layout		4Z	1Z	2Z
Contact capacity	AC	3A 250V	15A 250V	10A 250V
	DC	3A 30V	15A 30V	10A 30V
Contact resistance(m)		≤50m	≤50m	≤50m
Insulation resistance(M)		≥100M	≥100M	≥100M
Dielectric strength	BOC	1000VAC	1000VAC	1000VAC
	BCC	1500VAC	1500VAC	1500VAC
Coil nominal voltage	AC	6 to 240V	6 to 240V	6 to 240V
	DC	6 to 220V	6 to 220V	6 to 220V
Coil nominal power	AC	0.9VA to 1.2VA	0.9VA to 1.2VA	0.9VA to 1.2VA
	DC	≤0.9W	≤0.9W	≤0.9W
Electrical life(OPS)		10 ⁵	10 ⁵	10 ⁵
Mechanical life(OPS)		10 ⁷	10 ⁷	10 ⁷
Operating temperature(°C)		-40~+60	-40~+60	-40~+60
Weight(g)		≤35	≤35	≤35
Mounting methods		Printed-circuit board, Outlet	Printed-circuit board, Flange, Outlet	Printed-circuit board, Flange, Outlet