



ASTP



ASTP



AH 2



AH 2

Classification		Timer		Timer		Timer	
Specification Model		ASTP-N		ASTP-Y		AH2-N	
Dimension		61H × 49W × 70D		88H × 58W × 68D		61H × 49W × 70D	
Mounting & Socket	Surface(-N)	PF083A PS-08		PF083A		PF083A PS-08	
	Flush(-Y)	P2CF-08		US-08 P3G-08		P2CF-08	
Full Timing Range		SEC: 1,3,6,10,12,30,60 MIN: 3,6,10,12,30,60 HR: 3,6,10,12,24		SEC: 1,3,6,12,30,60 MIN: 3,6,12,30,60 HR: 3,6,12,24			
Rated Voltage (V)		AC: 12,24,110,220,240 50/60Hz DC: 12,24				AC: 12,24,110,220,240 50/60Hz DC: 12,24	
Indicator Operating		Time Operating		ON-UP Two Indicator Lamp			
O/P Contact	Model	ASTP-N1/ ASTP-Y1	ASTP-N2/ ASTP-Y2	ASTP-N/ ASTP-Y	AH2-N1/ AH2-Y1	AH2-N2/ AH2-Y2	AH2-N/ AH2-Y
	Time Limit 1C	5A		5A	5A		5A
	Time Limit 2C		5A			5A	
	Instantaneous 1C			5A			5A
Life	Mechanical	5 × 10 ⁶ Times				5 × 10 ⁶ Times	
	Electrical	105 Times				105 Times	
Accuracy	Repeat Error	±1% max				±1% max	
	Setting Error	±10% max				±10% max	
	Voltage Error	±1% max				±1% max	
	Temp Error	±2% max				±2% max	
Reset Time		0.1 sec max				0.1 sec max	
Consumed Power		3VA				3VA	
Ambient temperature		-10°C~+55°C				-10°C~+55°C	
Ambient Humidity		48~85% RH				48~85% RH	
Weight		220g				220g	