



ASY



ST6P

Classification		Digital Timer	Digital Timer	Timer	
Specification Model		ASY-2D	ASY-3D	H3Y-(ST6P)	
Dimension		88H × 58W × 68D	88H × 58W × 68D	28H × 21W × 52.6D	
Mounting & Socket	Surface(-N)	PF083A	PF083A	PYF08A(E)	PYF14A(E)
	Flush(-Y)	US-08 P3G-08	US-08 P3G-08	With Y-20 adapter	
Full Timing Range		SEC: 9.9,99 MIN: 9.9,99 HR: 9.9,99	SEC: 9.99,99.9,999 MIN: 99.9,999 HR: 99.9,999	SEC: 1,3,5,10,30,60,120 MIN: 3,5,10,30,60 HR: 3	
Rated Voltage (V)		AC: 12,24,110,220,240 50/60Hz DC: 12,24	AC: 12,24,110,220,240 50/60Hz DC: 12,24	AC: 12,24,110,220,240 50/60Hz DC: 12,24	
Indicator Operating		After contact transfer	After contact transfer	Power, up Operating	
O/P Contact	Model	ASY-2D	ASY-3D		
	Time Limit 1C				
	Time Limit 2C	5A	5A		
	Instantaneous 1C				
Life	Mechanical	5 × 10 ⁶ Times	5 × 10 ⁶ Times	5 × 10 ⁶ Times	
	Electrical	105 Times	105 Times	105 Times	
Accuracy	Repeat Error	±0.05% max	±0.05% max	±3% max	
	Setting Error	0	0	-	
	Voltage Error	±0.05 Sec	±0.05 Sec	±2% max	
	Temp Error	±0.05 Sec	±0.05 Sec	±5% max	
Reset Time		0.3 sec max	0.3 sec max	0.2 sec max	
Consumed Power		5VA	5VA	3VA	
Ambient temperature		-10°C~+55°C	-10°C~+55°C	-10°C~+55°C	
Ambient Humidity		48~85% RH	48~85% RH	48~85% RH	
Weight		230g	230g	45g	