

This kind of product feature has high efficiency and low consumption. It can save a lot of power consumption and operating costs. The new S9 Series transformer is impoldered on the bas's of the 10KV Distribution transformer. It accords with the GB1094-96, GB/T 6451-99, IEC76 standard.



S9

Rated capacity (KVA)	Voltage			connection group	Loss		unload current(%)	resistant voltage	weight			Measure(MM)			Distance of Din rail
	high-voltage(kv)	extend connection	low-voltage(kv)		unload	load			empty weight	oil weight	total weight	length(L)	width(W)	height(H)	
10	6 6.3 10 10.5 11	±5% (±2×2.5%)	0.4	Yyn0 or Dyn11	65	330	3.5	4	90	35	150	760	400	950	350×350
20					105	480	3.0		135	60	225	885	400	955	350×350
30					130	600	2.1		180	70	285	985	380	1015	400×400
50					170	870	2.0		230	75	350	985	510	1035	400×450
63					200	1040	1.9		285	90	430	1060	465	1135	400×450
80					250	1250	1.8		295	95	475	1010	775	1070	400×450
100					290	1500	1.6		330	100	520	1010	740	1095	400×450
125					340	1800	1.5		380	110	600	1040	770	1135	400×550
160					400	2200	1.4		440	120	685	1235	735	1165	550×550
200					480	2600	1.3	4.5	515	135	800	1280	765	1210	550×550
250					560	3050	1.2		610	160	940	1345	800	1315	550×550
315					670	3650	1.1		715	180	1105	1395	850	1375	660×660
400					800	4300	1.0		880	205	1310	1435	820	1460	660×660
500					960	5150	1.0		1005	230	1515	1525	965	1450	660×660
630					1200	6200	0.9		1155	265	1770	1615	1080	1615	660×660
800					1400	7500	0.8		1420	315	2160	1700	1120	1705	820×820
1000					1700	10300	0.7		1580	425	2520	1750	1140	1880	820×820
1250					1950	12000	0.6		1940	495	3040	1850	1245	1835	820×820
1600					2400	14500	0.6		2355	560	3800	1865	1285	2020	820×820
2000					2600	17000	0.5	5	3165	755	4950	2300	1165	2305	1070×1070
2500					3000	20700	0.5		3880	1300	6580	2440	1315	2490	1070×1070