

Dx Series:

Model DX-20, DX-30, DX-40 are available for connecting with cable, and also available for connecting with bus bar.

Maximum voltage: 0.66KV
 Frequency: 50-60Hz
 Class: 1.0
 Short-time thermal current: $I_{th}=60I_h$
 Mounting methods: either by din rail (35mm) or by screws
 Window dimensions : diameter 22mm (DX-20, DX-20L)
 31×10mm (DX-30, DX-30L)
 41×10mm (DX-40)

Technical data& Specification:

Model	Primary/ secondary	Busbar Hole Dimension (MM)	Rated Burden (VA)	Class	Rated Voltage
DX-20	50/5A-150/5A	f=20mm	1.5-2.5	1.0	660V
DX-30	100/5A-500/5A	30×10mm	1.5-2.5	1.0	660V
DX-40	150/5A-1000/5A	40×10mm	3-10	1.0	660V
DX-20L	50/5A-150/5A	f=20mm	1.5-2.5	1.0	660V
DX-30L	100/5A-500/5A	30×10mm	1.5-2.5	1.0	660V

Dimension of case (mm):

Model	A	B	C	D	E
DX-20	53	28	57	66	54
DX-30	53	28	57	66	54
DX-40	71	45	73	81	65
DX-20L	53	28	57	66	54
DX-30L	53	28	57	66	54

Outline Drawing:

