



CDS servers:

Primary current:
Secondary approval:
Standard current:
Maximum voltage:
Frequency:
Rated load:

Class:

Short-time thermal current:

Rated security coefficient:

-High fire retardancy and security

-Wide range of sizes to accommodate all the existing installations



Specification:

Model	Primary / secondary (A)
CDS-40	100/5, 150/5, 200/5, 250/5, 300/5, 400/5, 500/5, 600/5A
CDS-60	300/5, 400/5, 500/5, 600/5, 750/5, 800/5, 1000/5, 1200/5A
CDS-80	500/5, 600/5, 750/5, 800/5, 1000/5, 1200/5, 1500/5, 1600/5A
CDS-100	600/5, 750/5, 800/5, 1000/5, 1200/5, 1500/5, 1600/5, 2000/5A, 2500/5, 3000/5A
CDS-120	1000/5, 1200/5, 1500/5, 1600/5, 2000/5, 2500/5, 3000/5, 4000/5A, 5000/5



Dimension of case (mm):

Model	Dimensions			Busbar hole dimension		Installation dimension
	W	H	D	A	E	M
DS-40	75	105	45	42	32	45
DS-60	98	116	45	62	32	42
DS-80	118	120	45	82	32	60
DS-100	140	130	49	102	32	80
DS-120	165	152	49	122	53	80



Outline Drawing:

