



1.Application

Insulation/continuity resistance measurement of electric equipment in repairing,testing or inspecting.

2.Features

- Three rated output voltages available for insulation test
- 1mA short circuit current on insulation test
- 200mA short circuit current on continuity test
- 3 ½ LCD digital display for easy reading.
- Low power consumption and powered by 6×1.5V battety(R6 or Lr6).
- Low battery warning with sign " " on LCD.
- Portable and easy-to-operate.

3. Insulation Resistance

Rated Voltage	250V;500V;1000V
Open Circuit Voltage	Rated Voltage(+20 % - 0 %)
Measuring Range	(0~19.99) M Ω;(0~199.9)M Ω
Accuracy	±(5 % RDG+2d)
Short Circuit Current	≥ 1mA

4.Continuity

Open Circuit Voltage	4V ~ 7V
Measuring Range	(0~19.99) Ω (0~199.9) Ω
Accuracy	±(5 % RDG+2d)
Short Circuit Current	≥ 200mA

Withstand Voltage	AC3KV 50Hz 1min
Operating Temperature&Humidity	0°C~40°C; < 85% RH
Power Supply	6×1.5V(R6 or LR6) Battery
Dimensions	190 mm (L) × 110 mm (W) × 58 mm (D)
Weight	≈ 0.5kg