

LW26 Series Rotary Switches




4. Dimensions

Dimensions and installation


Square escutcheon plate and rectangular escutcheon plate



LW26-20



LW26-10
Installation



LW26-160
Installation



LW26-32

Description	Escutcheon plate	Dimension(mm)				Installation(mm)			
		A	B	C	L	E	F	D1	D2
LW26-10	M0 square	30	30	28	22+8n	20		ø8	ø3.2
LW26X-10	M0 square	30	30	28	26.5+12n	20		ø8	ø3.2
LW26-20	M1 square	48	48	43	22+9.6n	36	36	ø8.5	ø4.5
	M1 rectangular	48	60	43	22+9.6n	36	36	ø8.5	ø4.5
	M2 square	64	64	43	25+9.6n	48	48	ø10	ø4.5
	M2 rectangular	64	80	43	25+9.6n	48	48	ø10	ø4.5
LW26X-20	M1 square	48	48	46	22+14n	36	36	ø8.5	ø4.5
	M1 rectangular	48	60	46	22+14n	36	36	ø8.5	ø4.5
	M2 square	64	64	46	25+14n	40	40	ø10	ø4.5
	M2 rectangular	64	80	46	25+14n	48	48	ø10	ø4.5
LW26-25	M1 square	48	48	45.2	23+12.8n	36	36	ø8.5	ø4.5
	M1 rectangular	48	60	45.2	23+12.8n	36	36	ø8.5	ø4.5
	M2 square	64	64	45.2	26.5+12.8n	48	48	ø10	ø4.5
	M2 rectangular	64	80	45.2	26.5+12.8n	48	48	ø10	ø4.5
LW26-32	M2 square	64	64	58	29.2+12.8n	48	48	ø10	ø4.5
	M2 rectangular	64	80	58	29.2+12.8n	48	48	ø10	ø4.5
LW26-32F	M1 square	48	48	48	23+14n	36	36	ø8.5	ø4.5
	M1 rectangular	48	60	48	23+14n	36	36	ø8.5	ø4.5
	M2 square	64	64	48	24.5+14n	48	48	ø10	ø4.5
	M2 rectangular	64	80	48	24.5+14n	48	48	ø10	ø4.5
LW26-63	M2 square	64	64	66	29.2+21.5n	48	48	ø10	ø4.5
	M2 rectangular	64	80	66	29.2+21.5n	48	48	ø10	ø4.5
	M3 square	88	88	66	29.2+21.5n	68	68	ø13	ø4.5
	M3 rectangular	88	107	66	29.2+21.5n	68	68	ø13	ø4.5
LW26-125	M3 square	88	88	84	35+26.5n	68	68	ø13	ø6
	M3 rectangular	88	107	84	35+26.5n	68	68	ø13	ø6
LW26-160	M3 square	88	88	88	35+26.5n	68	68	ø13	ø6
	M3 rectangular	88	107	88	35+26.5n	68	68	ø13	ø6

LW26 Series Rotary Switches

1. Working Conditions

Ambient temperature Do Not exceed 40°C and the average temperature, measured over a period of 24 hours, Do Not exceed 35°C.

Ambient temperature should not be below -5°C.

Should not be installed over 2000m above sea level.

The humidity should not exceed 50% when the ambient temperature is 40°C and higher humidity is allowed for lower temperature.



LW26-20







LW26-32

2. Installation Conditions

A clean environment is required.

Please follow our manual.

3. Escutcheon plate and handle

Escutcheon plate	Type of handle	Color	Escutcheon plate M0 M1 M2 M3	Type of handle	Color	Escutcheon plate M0 M1 M2 M3
M0 	R Type 	Black Red White Gray		I Type 	Black Red White Gray Yellow	
M1 	F Type 	Black Red White Gray		B Type 	Black Red White Gray	
M2 	H Type 	Black Red White Gray		L Type 	Black Red White Gray	
M3 	P Type 	Black Red White Gray		K Type 	Black Red White Gray	