



Types		Rated voltage(V)	Rate current(A)	Weight(g)	Dimension(mm)		
General (gG)	Equivalents				A	B	φD
RM1-30	--	250	30	17.7	50.8	12.7	14.3
RM1-60	--	250	60	40.3	76.2	15.9	20.6
RM2-30	RF30	250	20-30	18	51	12.7	14.0
RM2-60	RF60	250	60	53	77	19.7	20.2
RM3-30	RFS30	600	30	87	128	16.7	20.2
RM3-60	RFS60	600	60	125	140	20.7	25.7



Types		Rated voltage(V)	Rate current(A)	Weight(g)	Dimension(mm)			
General (gG)	Equivalents				A	B	φD	E
RM1-100	--	250	100	134	149.2	25.4	28.5	3.2
RM1-200	--	250	200	324.5	181	34.9	39.5	4.8
RM2-100	RF100	250	100	98	149	25	27	3
RM2-200	RF200	250	200	146	182	36.5	47.2	4.8
RM2-350	RF225-350	250	225-350	1251	220	51.8	55.5	6.4
RM2-500	RF450-500	250	450-500	1272	265	61	66.5	6.4
RM3-100	RFS100	600	100	246	202	26.2	37.6	3.2
RM3-200	RFS200	600	200	359	246	36.5	47.2	4.8
RM3-400	RFS225-400	600	225-400	1072	297	51.8	66.5	6.4
RM3-600	RFS450-600	600	450-600	1332	342	61	66.5	6.4