



Types				Rated voltage(V)	Rate current(A)	Weight(g)	Dimension(mm)
Ours		Equivalents					ΦD*L
General (gG)	Fast(aR)	General (gG)	Fast(aR)				
RO06	RS06	--	--	250/380	1-32	6.5	12.7*29
RO07	RS07	--	--	600	10-100	75	30*57
RO09	RS09	--	--	500	2-63	17.4	18*37
RO10	RS10	--	--	500	2-63	23.5	18*50
RO11	RS11	AJT JKS LPJ	ACL	600	2-32	51.5	21*58
RO12	RS12	AJT JKS LPJ	ACL	600	35-100	90	27*60
RO13	RS13	--	--	500	2-40	23.2	15*50
RO14	RS14	RT19-16g F1	--	500	0.5-20	4.4	8.5*31.5
RO14A	RS14A	--	--	250	0.5-20	3.5	8.5*23
RO14B	RS14B	--	--	380/500	0.5-20	5.0	8.5*36
RO15	RS15	RT14-20gF2RT18-32 RT19-25	KTK KLM	380/500	0.5-32	7.7	10.3*38
RO15A	RS15A	--	--	250	0.5-16	4.8	10.3*25.8
RO15B	RS15B	--	--	250/500	0.5-25	5.8	10.3*31.5
RO15C	RS15C	--	--	380/500	0.5-32	6.2	10.3*34
RO15D	RS15D	--	--	600	2-32	11	10.3*57
RO16	RS16	RT14-32gF3 RT18-63 RT19-40	EWP	380/660	2-50	20.5	14.3*51
RO16A	RS16A	--	--	500	2-50	15.6	14.3*38
RO16B	RS16B	--	--	500	2-50	18.5	14.3*45
RO16C	RS16C	--	--	500	2-50	27.5	14.3*67
RO17	RS17	RT14-63gF4 RT18-125 RT19-100	--	380/660	10-125	58	22.2*58
RO18	RS18	--	URE2263	380	0.5-25	4.8	9.6*30
RO19	RS19	FRS TRS FLSR	--	600	0.5-32	91.2	20.5*127
RO19A	RS19A	RLNR PC2	--	250/500	0.5-63	63	20.5*76
RO19B	RS19B	FRS TRS FLSR	--	600	0.5-32	85	20.5*114
RO19C	RS19C	--	--	600	32-63	172.4	27*139
RO19D	RS19D	--	--	600	32-63	160	27*147
RO54	RS54	--	--	250	0.5-16	1	5*20
RO55	RS55	--	--	250	0.5-16	1.3	5*25
RO56	RS56	--	--	250	0.5-16	1.7	6*20
RO57	RS57	--	--	250	0.5-16	2.1	6.3*25
RO58	RS58	--	--	250/500	0.5-16	2.5	6.3*31.5