



Types	Rated voltage(V)	Rate current(A)	Weight(g)	355Dimension(mm)						
				A	B	C	φD	E	F	φd
RS97G	500/660	200-400	341	146	110	76	41	29	5	7*9.5
RS97H	500/660	200-400	520	146	110	75	48	36	8	12.5*18
RS97K	500/660	200-400	480	130	100	70	53	42	8	14.2*18
RS97L	500	200-400	420	125	103	48	51	38	6	10.5*18
RS97M	500	400-500	465	145	102	53	51	38	6.3	14.5*30
RS97N	500/660	200-400	353	145	113	88	38	25	6.3	10.5*18
RS98A	500/660	600	635	165	114	56	64	50	8	10.5*18
RS98B	500/660	600	1280	170	130	80	70	50	6	10.5*18
RS98C	500/660	500	720	181	133	86	51	40	10	10.5*15
RS98D	500/660	600	970	180	131	85	64	50	10	14.2*18
RS98E	700	250-400	450	130	90	50	51	38	6.3	14.2*28
RS98F	700	300-400	780	181	130	72	64	50	10	14.2*28
RS98G	700	400-600	1135	175	135	73	63	51	10	12.5*18
RS98H	700	400-500	583	166	118	70	50	38	6	16.2*22
RS98K	700	500-600	996	181	114	50	64	51	9.5	14.2*45
RS98L	700	500-800	1100	167	137	72	70	50	8	10.5*18
RS98M	700	500-600	925	160	108	53	63	50	9	14.2*23
RS98N	700	500-600	1050	180	125	73	60	46	13	14.2*25
RS98P	500	400-500	410	110	80	53	50	40	6	10.5*18
RS99A	500/660	500-600	1058	190	140	90	65	50	10	14.2*18
RS99B	500/660	400-600	1410	203	152	95	64	50	10	10.5*18
RS99C	500/660	400-600	1420	217	157	101	60	50	12	16.2*28
RS99D	500	800-1000	1786	180	127	85	76	61	11.3	16.2*22
RS99E	700	800-1250	1920	200	150	100	90	70	13	20.5*30
RS99F	700	400-600	1200	180	129	72	64	51	9.5	13.5*18
RS99G	700	800-1000	1830	195	150	95	75	61	10	13*18
RS99H	500	500-600	560	145	130	46	52	38	8	15*29
RS99J	500	400-600	962	175	123	70	65	50	10	14.2*30
RS99K	500	400-600	1023	181	133	72	64	51	10	13*33
RS99L	500	400-600	1010	175	125	71	65	50	10	14.2*33