



Type	Rated Voltage(KT)	MCOV(KT)	sparkover voltage(KT)		8/20 μ s Lightning Impulse residual voltage(KV)	2000 μ s square wave impulse current withstand	4/ μ s high current impulse
			Power frequency	1.2/50 μ s Lightning impulse			
Y5C-3	3	2.55	5.0	7.8	9	100	65
Y5C-6	6	5.1	10.0	15.5	18	100	65
Y5C-9	9	7.65	16.5	24.5	27	100	65
Y5C-12	12	1.2	21.0	32.6	36	100	65
Y5C-15	15	12.7	25.0	38.8	45	100	65
Y5C-18	18	15.3	31.0	48.1	54	100	65
Y5C-21	21	17.0	34.0	52.7	63	100	65
Y5C-24	24	19.2	39.0	60.5	72	100	65
Y5C-27	27	21.9	45.0	69.8	81	100	65
Y5C-30	30	24.4	50.0	77.5	90	100	65
Y5C-33	33	26.8	55.0	85.3	99	100	65
Y5C-36	36	29	60.0	93.0	108	100	65
Y5C-42	42	34.1	70.0	108.5	126	100	65

Type	Rated Voltage(KT)	MCOV(KT)	sparkover voltage(KT)		8/20 μ s Lightning Impulse residual voltage(KV)	2000 μ s square wave impulse current withstand	4/ μ s high current impulse
			Power frequency	1.2/50 μ s Lightning impulse			
Y5C-3	3	2.55	9.5	7.7	9	1	100
Y5C-6	6	5.1	19.5	15.4	18	1	100
Y5C-9	9	7.65	28.5	23.1	27	1	100
Y5C-12	12	1.2	38.0	30.8	36	1	100
Y5C-15	15	12.7	47.5	38.5	45	1	100
Y5C-18	18	15.3	57.0	46.2	54	1	100
Y5C-21	21	17.0	66.5	53.9	63	1	100
Y5C-24	24	19.2	76.0	61.6	72	1	100
Y5C-27	27	21.9	85.5	69.3	81	1	100
Y5C-30	30	24.4	95.0	76.5	90	1	100
Y5C-33	33	26.8	104.5	84.7	99	1	100
Y5C-36	36	29	114.0	92.4	108	1	100
Y5C-42	42	34.1	132.3	100.1	126	1	100

