

SM Insulating Connector




Values	Style					
	SM-25	SM-30	SM-35	SM-40	SM-51	SM-76
Tensile strength (1bs)	500	550	600	650	1000	1500
Tongue strength (ft 1bs)	6	8	10	10	20	40
Voltage withstand (kv)	6	8	10	12	15	25
Screw (mm)	6	8	8	8	8	10
Weight (g)	28	44	50	86	83	233



UK Terminal Block

SM



USLKG 4N



USLKG 6N



USLKG 10N



USLKG 16N



UK 2.5N




UK 3N



UK 5N



UK 10N



UK 16N

Model	Hard Wire (mm ²)	Soft Wire (mm ²)	Rated Current (A)	Rated Voltage (V)	Dimension (mm)
UK2.5B	0.2-4	0.2-2.5	32	690	6.2 x 42.5 x 42
UK3N	0.2-4	0.2-2.5	32	800	6.2 x 42.5 x 42
UK5N	0.2-6	0.2-4	41	800	6.2 x 42.5 x 47
UK6N	0.2-10	0.2-2.5	57	800	6.2 x 42.5 x 47
UK10N	0.5-16	0.5-10	76	800	10.2 x 42.5 x 47
UK16N	2.5-25	4-16	101	800	12.2 x 42.5 x 54
UK35N	0.75-50	0.75-35	150	1000	15.2 x 50.0 x 62
UKH50	16-50	25-50	150	1000	20 x 70.5 x 83.5
UKH95	25-95	35-95	232	1000	25 x 83 x 97.5
UKH150	35-150	50-150	309	1000	31 x 100 x 118.5

Model	Hard Wire (mm ²)	Soft Wire (mm ²)	Rated Current (A)	Dimensions (mm)
USLKG2.5	0.2-4	0.2-2.5	32	6.2 x 42.5 x 42
USLKG3	0.2-4	0.2-2.5	32	6.2 x 42.5 x 47
USLKG5	0.2-6	0.2-4	41	6.2 x 42.5 x 47
USLKG6N	0.2-10	0.2-6	57	8.2 x 42.5 x 47
USLKG10N	0.5-16	0.5-10	76	10.2 x 42.5 x 47
USLKG16N	2.5-25	4-16	101	12.2 x 42.5 x 54
USLKG35N	0.75-50	0.75-35	150	15.2 x 50.0 x 62
USLKG50	16-50	25-50	150	20 x 70.5 x 81.5