

## B Wintersweet Shaped Copper Jointing Clamp

### 1. Application

It is suitable for transition connection of electronic apparatus with wire and cable in indoor distribution equipment, made of brass by die cast and coated nickel.

### 2. Specifications

| Type     | L  | A  | B  | d   |
|----------|----|----|----|-----|
| B16-25   | 37 | 10 | 21 | 7.5 |
| B25-35   | 48 | 13 | 22 | 11  |
| B50-70   | 60 | 17 | 31 | 11  |
| B120-150 | 70 | 23 | 35 | 15  |
| B210-250 | 90 | 30 | 46 | 17  |



## GT Copper Cable Connector

### 1. Application

GT series copper cable connectors are applicable for the connection of the circular wire with power supply cable in distribution equipment. They are made of tin coated 99.9% pure copper tube.

### 2. Specifications

| Type    | D (mm) | d (mm) | L (mm) |
|---------|--------|--------|--------|
| GT-1.5  | 3.7    | 1.8    | 20     |
| GT-2.5  | 4      | 2.5    | 20     |
| GT-4    | 4.8    | 3.1    | 20     |
| GT-5.5  | 5.5    | 3.8    | 25     |
| GT-10   | 6.8    | 4.8    | 30     |
| GT-16   | 7.5    | 5.5    | 35     |
| GT-25   | 9      | 7      | 40     |
| GT-35   | 10.5   | 8.2    | 45     |
| GT-50   | 12.5   | 9.8    | 50     |
| GT-70   | 14.5   | 11.5   | 55     |
| GT-95   | 17.5   | 13.5   | 60     |
| GT-120  | 19.5   | 15     | 65     |
| GT-150  | 21     | 16.5   | 70     |
| GT-85   | 23.5   | 18.5   | 75     |
| GT-240  | 26.5   | 21     | 80     |
| GT-300  | 30     | 24     | 85     |
| GT-400  | 34     | 27     | 90     |
| GT-500  | 38     | 30     | 100    |
| GT-630  | 45     | 35     | 110    |
| GT-800  | 50     | 39     | 150    |
| GT-1000 | 56     | 44     | 170    |

