

1.Specification

Material: Nylon 66, 94V-2 with UL approval.

Usage: Peel the coat of wire, then insert to tube, use pincers to fix them.

Feature: Nylon shell, long copper tube, easy to conduct electricity and hold wire tightly.



P6

ITEM.NO.	A(mm)	W		D(mm)	Suitable Wires	
		B(mm)	C(mm)		mm ²	AWG
P6-3	17.8	7.2	3.6	2.5	1.25	22-16
P6-4	21.0	8.2	4.0	2.9	2	16-14
P6-5	22.5	9.0	4.8	3.9	5.5	12-10
P6-6	25.0	10.0	5.6	4.5	8	8
P6-7	24.2	11.0	6.5	5.4	10	8-6
P6-8	25.6	11.8	7.5	6.0	13	6
P6-10	29.5	13.5	9.3	7.5	16	4

1.Specification

Material: Nylon 66, with spring inside.

Usage: peel wire coat, insert the wire in, then tighten.



P7

Item.No.	H (mm)	W (mm)	D (mm)	Suitable Wire (mm)
P7-1	15	8.7	6.5	MIN#20 x 1+#22 x 1, MAX#16 x 2
P7-2	18	10.0	7.5	MIN#20 x 3, MAX#16 x 3
P7-3	23	11.2	9.5	MIN#20 x 3, MAX#16 x 3+#18 x 1
P7-4	24.2	13.6	10.8	MIN#14 x 1+#18 x 1, MAX#14 x 4+#18 x 1
P7-5	27.8	16.1	12.7	MIN#14 x 2, MAX#10 x 2+#12 x 2

1.Specification

Material: Nylon 66, with spring inside.

Usage: peel wire coat, insert the wire in, then tighten.



P8

Item.No.	H (mm)	W (mm)	D (mm)	Suitable Wire (mm)
P7-1	15	8.7	6.5	MIN#20 x 1+#22 x 1, MAX#16 x 2
P7-2	18	10.0	7.5	MIN#20 x 3, MAX#16 x 3
P7-3	23	11.2	9.5	MIN#20 x 3, MAX#16 x 3+#18 x 1
P7-4	24.2	13.6	10.8	MIN#14 x 1+#18 x 1, MAX#14 x 4+#18 x 1
P7-5	27.8	16.1	12.7	MIN#14 x 2, MAX#10 x 2+#12 x 2