

Copper-conductor PVC insulation shielded PVC sheathed flexible wire(flame retardant)

The products can be applied to wiring system that requires anticlutter such as building automation control system, guard against theft and alarm system, fire-fighting system, three-meter autotranscription system, communications, audio frequency, audio system, instruments, electronic equipment, automated assembly and so on.

Product standard: JB8734.5-1998

Technical parameter



core cross-section(mm ²)	construction(NO/mm)	insulation	Sheath	Average o.d.		The MAX resistance in 20°C MQ/KM	The min insulation resistance MQ/KM
		Standard width(mm)	Standard width(mm)	Min(mm)	Max(mm)		
2×0.12	7/0.15	0.4	3.7	3.7	4.9	158.0	0.016
2×0.2	12/0.15	0.4	4.1	4.1	5.3	92.3	0.013
2×0.3	16/0.15	0.5	4.8	4.8	6.2	69.2	0.014
2×0.4	23/0.15	0.5	5.1	5.1	6.6	48.2	0.013
2×0.5	28/0.15	0.5	5.3	5.3	6.8	39.0	0.012
2×0.75	42/0.15	0.5	5.8	5.8	7.4	26.0	0.010
2×1.0	32/0.20	0.6	6.4	6.4	8.2	19.5	0.010
2×1.5	48/0.2	0.8	7.3	7.3	9.2	13.3	0.009