

1. Features

- Replaces many type 117 contactors used by OEM's
- Universal style mounting bracket fits existing mounting holes
- Screw terminals and 1/4 quick connect terminals for easy installation

2. Specifications

Temperature range	-40°F to 150°F
Mechanical life (no load)	Conforms to UL and ARI specifications
Electric life	Conforms to UL and ARI specifications 94-388 thru 94-390 achieve 200,000 cycles, make LRA at .5 pf, break 125% of FLA at .75 pf at rated voltage, 10,000 cycles make and break LRA at .5 pf rated voltage 94-394 thru 94-396 achieve 100,000 cycles, make LAR at .5 pf at rated voltage 6,000 cycles make and break LRA at .5 pf rated voltage
Weight (approximate)	9.25 oz
Coils Frequency	50/60Hz
Coil insulation	Class B(130°C)
Termination	Screw and double 1/4 Q.C.
Operate	85% of nominal coil voltage; 110% maximum safe operate
Duty cycle	Continuous



3. Coil data

Steveco Number	Voltage AC	Res DC OHMS	Current MA	Nominal VA	Max. inrush
30 Amp 40Amp					
AMC2-388 AMC2-394	24	16.5	208	5	20
AMC2-389 AMC2-395	120	420	42	5	20
AMC2-390 AMC2-396	208/240	1825	21	5	20

4. Contact ratings

Type	Voltage	FLA	LRA	RES
AMC2-388 thru AMC2-390	277	30	150	40
	480	0	75	40
	600	30	50	40
AMC2-394 thru AMC2-396	277	40	200	50
	480	40	100	50
	600	40	80	50

